

3" Radiance™ LED Overhead Light



Features

- Air flow vents added to dissipate heat
- Polycarbonate lens provides the appearance of frosted glass while offering maximum light output and a soft diffused glow
- Available with or without an integral on/off switch
- Color control technology guarantees the color difference between lights is undetectable to the human eye
- RGB(W) option contains a lockout circuit to prevent the white and RGB LEDs from being on at the same time

Product Details

Mounting	Surface	Recessed	
Lens Material	Polycarbonate		
Voltage	13.6V DC		
Wattage	Std: 2.3W High: 2.8W	2.6W	2.1W
Currents	Std: 0.17A High: 0.2A	0.21A	0.16A
Lumens	Std: 150LM High: 224LM	160LM	170LM
Color Temp.	3000K, 3500K or 4000K	3000K or 4000K	RGB/3000K, RGB/3500K or RGB/4000K
Cutout Dimensions	N/A	2.25"	
Listing	CSA		

Specification Guide

Sample Part #: 69453CUSM-01-0030

Base Part	
Switch Option	
Mounting Style	
Type of LEDs	
Color Temperature	

3" Surface Mount Radiance

Base Part #	Switch Option	Mounting Style	Type of LEDs	Color Temp.
69453C	U - Unswitched S - Switched	SM - Surface Mount	01 - Standard 02 - High	0030 - 3000K 0035 - 3500K 0040 - 4000K

3" Recessed Radiance

Base Part #	Mounting Style	Type of LEDs	Color Temp.
69231PC	NS - Screw Mount - Leave blank for spring mount	9 - Standard	3KE - 3000K 4KE - 4000K
	SP - Spring Mount LS - Leaf Spring NS - Screw Mount		RGB30 - RGB/3000K RGB35 - RGB/3500K RGB40 - RGB/4000K

