

Frontier™ Edge

Integrated LED Illuminated Mirror



Features

- Improved illumination and reduced shadowing through the use of forward facing lighting
- Safety PVC membrane on back prevents small pieces from falling off in the event of a mirror breakage
- Lead free silver backing exceeds ISO 9227:2012, 120 hour corrosion testing
- Can be mounted either portrait or landscape orientation
- Back box power supply provides flexible installation that meets stringent building codes
- Optional dimming and anti-fog mat add-on features
- Warm-to-cool white color selection enhances design

Product Details

Part #	69455.ELS.3226.30K.RMT	69455.ELS.2436.30K.RMT	69455.ELS.3927.30K.RMT	69455.ELS.1844.30K.RMT	690010.121 - 0-10V Dimming 690010.143 - Line Voltage 690010.143-2 - Line Voltage w/ Plug
Dimensions	31.5"W x 25.6"H x 1.8"D	23.6"W x 35.4"H x 1.8"D	39.4"W x 27.6"H x 1.8"D	18.1"W x 44"H x 1.8"D	13"L x 1.25"W x 1.7"D
Mounting Frame/ Housing	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Wattage	23W	24W	26W	25W	Output: 96W Max
Voltage	24V DC	24V DC	24V DC	24V DC	Input: 120 - 277V AC
Current	0.23A	0.24A	0.26A	0.25A	Output: Max 4A
Lumens	2650LM	2750LM	3025LM	2850LM	N/A
Color Temp.	3000K	3000K	3000K	3000K	N/A
Power Factor	N/A	N/A	N/A	N/A	0.94 @ 120V AC
Frequency	N/A	N/A	N/A	N/A	50 - 60Hz




3030 Corporate Grove Dr.
Hudsonville, MI 49426
Phone: 616.396.1355
itc-us.com

REV: 011525

Product Details Cont.

Part #	69455.ELS.2448.30K.RMT	69455.ELS.5626.30K.RMT	69455.ELS.5442.30K.RMT	69455.ELS.6642.30K.RMT
Dimensions	23.6"W x 47.2"H x 1.8"D	55.1"W x 25.6"H x 1.8"D	53.1"W x 41.3"H x 1.8"D	65"W x 41.3"H x 1.8"D
Mounting Frame	Aluminum	Aluminum	Aluminum	Aluminum
Wattage	23W	33W	38W	43W
Voltage	24V DC	24V DC	24V DC	24V DC
Current	0.29A	0.33A	0.38A	0.43A
Lumens	3300LM	3750LM	4400LM	4950LM
Color Temp.	3000K	3000K	3000K	3000K



Line Voltage Approved Dimmers

Leviton		Lutron	
VPI06-1LZ	DZ6HD	SCL-153PR	CTCL-153PDH
TTI06-1LZ	6674	DVCL-153PR	PD-6WCL
IPL06	6672	DVWCL-153PH	PD-5NE-WH

Specification Guide

Sample Part #: 69455.ELS.3226.30.RMT-AB

Base Part #	
Size	
Color Temperature	
Power Supply	
Optional Add-Ons	

Base Part #	Size	Color Temp.	Power Supply	Optional Add-Ons
Standard Stock Mirrors				
69455.ELS	3226 - 32"W x 26"H 2436 - 24"W x 36"H 3927 - 39"W x 27"H 1844 - 18"W x 44"H 2448 - 24"W x 48"H 5442 - 54"W x 42"H 5626 - 56"W x 26"H 6642 - 66"W x 42"H	30 - 3000K	RMT - No Power Supply	N/A
Custom Mirrors				
69455.ELS	3226 - 32"W x 26"H 2436 - 24"W x 36"H 3927 - 39"W x 27"H 1844 - 18"W x 44"H 2448 - 24"W x 48"H 5442 - 54"W x 42"H 5626 - 56"W x 26"H 6642 - 66"W x 42"H	30 - 3000K 35 - 3500K 40 - 4000K 00 - Unlit AA - Warm to Cool 3A - 3000K + Amber 3B - 3500K + Amber 4A - 4000K + Amber	RMT - No Power Supply 001 - 0-10V Power Supply ³ 002 - Line Voltage Power Supply ³	A - Dimming B - Anti-Fog AB - Dimming + Anti-Fog

1. Power Supplies are ordered separately
2. Custom mirrors require MOQ and lead time, contact sales for more info
3. Power supplies will come pre-installed on mirrors with an anti-fog mat
4. 270-00228 - Optional 30°, 90°, 120V, 3-prong plug

Notes:

1. Lumens based on light source
2. Standard non-stock mirrors subject to 90 day lead time
3. Custom mirrors available upon request, subject to a 50 piece minimum, 50% deposit and 90 day lead time following approved drawings
4. Warranty: 10-year frame and structure - 7-year glass, power supply and LEDs

